

ITW Performance Polymers

SAFETY DATA SHEET

MA830 ACTIVATOR

Commission Regulation (EU) No 2015/830 of 28 May 2015.

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name MA830 ACTIVATOR
UFI UFI: RT90-J0GS-G005-7PJ1

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Activator.

1.3. Details of the supplier of the safety data sheet

Supplier ITW Performance Polymers
Bay 150
Shannon Industrial Estate
Co. Clare
Ireland
V14 DF82
353(61)771500
353(61)471285
customerservice.shannon@itwpp.com

1.4. Emergency telephone number

Emergency telephone +44(0)1235 239 670 (24h)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (EC 1272/2008)

Physical hazards Not Classified
Health hazards Skin Irrit. 2 - H315 Eye Irrit. 2 - H319 Skin Sens. 1 - H317
Environmental hazards Aquatic Chronic 2 - H411
Human health Contains epoxy constituents. May produce an allergic reaction.

2.2. Label elements

Hazard pictograms



Signal word Warning

Hazard statements H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.
H411 Toxic to aquatic life with long lasting effects.

MA830 ACTIVATOR

Precautionary statements	P273 Avoid release to the environment. P280 Wear protective gloves/ protective clothing/ eye protection/ face protection. P302+P352 IF ON SKIN: Wash with plenty of water. P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P333+P313 If skin irritation or rash occurs: Get medical advice/ attention. P501 Dispose of contents/ container in accordance with national regulations.
Contains	BENZOYL PEROXIDE, EPOXY RESIN (Number average MW ≤ 700)
Supplementary precautionary statements	P261 Avoid breathing vapour/ spray. P264 Wash contaminated skin thoroughly after handling. P272 Contaminated work clothing should not be allowed out of the workplace. P321 Specific treatment (see medical advice on this label). P332+P313 If skin irritation occurs: Get medical advice/ attention. P337+P313 If eye irritation persists: Get medical advice/ attention. P362+P364 Take off contaminated clothing and wash it before reuse.

2.3. Other hazards

SECTION 3: Composition/information on ingredients

3.2. Mixtures

BENZOYL PEROXIDE			10-30%
CAS number: 94-36-0	EC number: 202-327-6		
Classification Org. Perox. B - H241 Eye Irrit. 2 - H319 Skin Sens. 1 - H317			
EPOXY RESIN (Number average MW ≤ 700)			10-30%
CAS number: 25068-38-6	EC number: 500-033-5	REACH registration number: 01-2119456619-26-0000	
Classification Skin Irrit. 2 - H315 Eye Irrit. 2 - H319 Skin Sens. 1 - H317 Aquatic Chronic 2 - H411			
TITANIUM DIOXIDE			5-10%
CAS number: 13463-67-7	EC number: 236-675-5	REACH registration number: 01-2119489379-17-0000	
Classification Carc. 2 - H351			

MA830 ACTIVATOR

Diisodecyl phthalate		5-10%
CAS number: 26761-40-0	EC number: 247-977-1	
M factor (Acute) = 1	M factor (Chronic) = 1	
Classification		
Aquatic Acute 1 - H400		
Aquatic Chronic 1 - H410		

The full text for all hazard statements is displayed in Section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation	Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Get medical attention if any discomfort continues.
Ingestion	Get medical attention immediately. Do not induce vomiting. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs.
Skin contact	Remove contaminated clothing immediately and wash skin with soap and water. Continue to rinse for at least 15 minutes. Get medical attention if irritation persists after washing.
Eye contact	Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 15 minutes and get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

General information	The severity of the symptoms described will vary dependent on the concentration and the length of exposure.
----------------------------	---

4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctor	Treat symptomatically.
-----------------------------	------------------------

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	Extinguish with carbon dioxide or dry powder. Do not use water jet as an extinguisher, as this will spread the fire.
-------------------------------------	--

5.2. Special hazards arising from the substance or mixture

Specific hazards	Protection against nuisance dust must be used when the airborne concentration exceeds 10 mg/m ³ . Oxides of carbon. Oxides of nitrogen.
-------------------------	--

5.3. Advice for firefighters

Special protective equipment for firefighters	Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing.
--	---

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions	No smoking, sparks, flames or other sources of ignition near spillage. Avoid inhalation of vapours and contact with skin and eyes.
-----------------------------	--

6.2. Environmental precautions

Environmental precautions	Do not discharge into drains or watercourses or onto the ground.
----------------------------------	--

6.3. Methods and material for containment and cleaning up

MA830 ACTIVATOR

Methods for cleaning up

Eliminate all sources of ignition. No smoking, sparks, flames or other sources of ignition near spillage. Provide adequate ventilation. Absorb spillage with non-combustible, absorbent material. Collect and place in suitable waste disposal containers and seal securely. Containers with collected spillage must be properly labelled with correct contents and hazard symbol.

6.4. Reference to other sections

Reference to other sections For waste disposal, see section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Usage precautions Keep away from heat, sparks and open flame. Avoid contact with skin and eyes.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions Store in tightly-closed, original container in a dry, cool and well-ventilated place. Store in closed original container at temperatures between 0°C and 40°C. Store away from incompatible materials (see Section 10).

7.3. Specific end use(s)

Specific end use(s) The identified uses for this product are detailed in Section 1.2.

SECTION 8: Exposure controls/Personal protection

8.1. Control parameters

Occupational exposure limits

BENZOYL PEROXIDE

Long-term exposure limit (8-hour TWA): WEL 5 mg/m³

Short-term exposure limit (15-minute): WEL

TITANIUM DIOXIDE

Long-term exposure limit (8-hour TWA): WEL 4 mg/m³ respirable dust

Long-term exposure limit (8-hour TWA): WEL 10 mg/m³ inhalable dust

WEL = Workplace Exposure Limit.

BENZOYL PEROXIDE (CAS: 94-36-0)

DNEL

Workers - Inhalation; Long term systemic effects: 11.75 mg/m³

Workers - Dermal; Long term systemic effects: 6.6 mg/kg/day

EPOXY RESIN (Number average MW <= 700) (CAS: 25068-38-6)

DNEL

Workers - Dermal; Short term systemic effects: 8.33 mg/kg/day

Workers - Inhalation; Short term systemic effects: 12.25 mg/m³

8.2. Exposure controls

Protective equipment



Appropriate engineering controls

Provide adequate general and local exhaust ventilation. Observe any occupational exposure limits for the product or ingredients.

Eye/face protection

Wear chemical splash goggles. Personal protective equipment for eye and face protection should comply with European Standard EN166.

MA830 ACTIVATOR

Hand protection	Chemical-resistant, impervious gloves complying with an approved standard should be worn if a risk assessment indicates skin contact is possible. The most suitable glove should be chosen in consultation with the glove supplier/manufacturer, who can provide information about the breakthrough time of the glove material. To protect hands from chemicals, gloves should comply with European Standard EN374. The selected gloves should have a breakthrough time of at least 8 hours.
Other skin and body protection	Wear chemical protective suit.
Hygiene measures	Provide eyewash station and safety shower. No specific hygiene procedures recommended but good personal hygiene practices should always be observed when working with chemical products.
Respiratory protection	If ventilation is inadequate, suitable respiratory protection must be worn. Respirator selection must be based on exposure levels, the hazards of the product and the safe working limits of the selected respirator. Wear a respirator fitted with the following cartridge: Organic vapour filter. Check that the respirator fits tightly and the filter is changed regularly. Half mask and quarter mask respirators with replaceable filter cartridges should comply with European Standard EN140.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance	Viscous liquid.
Colour	Grey.
Odour	Slight.
Melting point	Not determined.
Initial boiling point and range	Not determined.
Flash point	Not determined.
Upper/lower flammability or explosive limits	Not determined.
Vapour pressure	Not determined.
Vapour density	Not determined.
Relative density	1.0-1.25 @ °C
Solubility(ies)	Slightly soluble in water.
Auto-ignition temperature	Not determined.

9.2. Other information

Other information	Not available.
Volatile organic compound	This product contains a maximum VOC content of <50 g/litre.

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity	The following materials may react violently with the product: Strong oxidising agents.
-------------------	--

10.2. Chemical stability

Stability	Unstable.
------------------	-----------

10.3. Possibility of hazardous reactions

MA830 ACTIVATOR

Possibility of hazardous reactions Not known.

10.4. Conditions to avoid

Conditions to avoid Avoid heat. Avoid contact with the following materials: Strong oxidising agents. Avoid contact with acids and alkalis.

10.5. Incompatible materials

Materials to avoid Strong alkalis. Strong oxidising agents. Strong acids.

10.6. Hazardous decomposition products

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Inhalation Irritating to respiratory system. Vapours may irritate throat/respiratory system. A single exposure may cause the following adverse effects: Coughing. Difficulty in breathing.

Ingestion May cause internal injury. Ingestion may cause severe irritation of the mouth, the oesophagus and the gastrointestinal tract. Gastrointestinal symptoms, including upset stomach.

Skin contact Irritating to skin. Prolonged and frequent contact may cause redness and irritation. May cause sensitisation by skin contact.

Eye contact Irritating to eyes. Repeated exposure may cause chronic eye irritation.

Acute and chronic health hazards The product contains an epoxy resin. May cause sensitisation or allergic reactions in sensitive individuals.

Route of exposure Inhalation Ingestion. Skin and/or eye contact

Target organs Eyes Skin Respiratory system, lungs

Toxicological information on ingredients.

BENZOYL PEROXIDE

Acute toxicity - oral

Acute toxicity oral (LD₅₀ mg/kg) 7,710.0

Species Rat

ATE oral (mg/kg) 7,710.0

TITANIUM DIOXIDE

Carcinogenicity

IARC carcinogenicity IARC Group 2B Possibly carcinogenic to humans.

SECTION 12: Ecological information

Ecotoxicity The product contains a substance which is harmful to aquatic organisms and which may cause long-term adverse effects in the aquatic environment.

12.1. Toxicity

Toxicity Not determined.

12.2. Persistence and degradability

Persistence and degradability The degradability of the product is not known.

MA830 ACTIVATOR

12.3. Bioaccumulative potential

Bioaccumulative potential Not determined.

12.4. Mobility in soil

Mobility The product is miscible with water and may spread in water systems.

12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB assessment This substance is not classified as PBT or vPvB according to current EU criteria.

12.6. Other adverse effects

Other adverse effects Not known.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

General information Waste should be treated as controlled waste. Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.

Disposal methods Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.

SECTION 14: Transport information

General The product is not covered by international regulations on the transport of dangerous goods (IMDG, IATA, ADR/RID).

14.1. UN number

No information required.

14.2. UN proper shipping name

No information required.

14.3. Transport hazard class(es)

No information required.

Transport labels

No transport warning sign required.

14.4. Packing group

No information required.

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant
No.

14.6. Special precautions for user

No information required.

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code No information required.

SECTION 15: Regulatory information

MA830 ACTIVATOR

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU legislation Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) (as amended).

15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

SECTION 16: Other information

Revision date	12/04/2021
Revision	12
Supersedes date	04/08/2017
Hazard statements in full	H241 Heating may cause a fire or explosion. H315 Causes skin irritation. H317 May cause an allergic skin reaction. H319 Causes serious eye irritation. H400 Very toxic to aquatic life. H410 Very toxic to aquatic life with long lasting effects. H411 Toxic to aquatic life with long lasting effects.

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.