

SAFETY DATA SHEET

Version #: 05

Issue date: 07-12-2019

Revision date: 08-03-2023

Supersedes date: 07-13-2023

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name or designation of the mixture PLEXUS® MA832 Adhesive

Registration number -

Synonyms None.

SKU# 0533

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Not available.

Uses advised against None known.

1.3. Details of the supplier of the safety data sheet

Company Name ITW Performance Polymers

Address Bay 150
Shannon Industrial Estate
Co. Clare
Ireland
V14 DF82

Contact Person Customer Service

Telephone Number 353(61)771500
353(61)471285

Email customerservice.shannon@itwpp.com

Emergency Phone Number 44(0) 1235 239 670 (24 hours)

1.4. Emergency telephone number

General in EU 112 (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)

Austria National Poisons Information Center +431 406 4343 (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)

Belgium National Poisons Control Center 070 245 245 (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)

Bulgaria National Toxicological Information Center +359 2 9154 233 (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)

Croatia Poisons Information Center +385 1 2348 342 (Hours of operation not provided. SDS/Product information may not be available for the Emergency Service.)

Cyprus Poison Center 1401 (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)

Czech Republic National Poisons Information Center +420 224 919 293, or +420 224 915 402 (Hours of operation not provided. SDS/Product information may not be available for the Emergency Service.)

Denmark National Poisons Control Center +45 82 12 12 12 (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)

Estonia National Poisons Information Center 16662 or abroad: (+372) 626 9390 (Monday 9:00AM to Saturday 9:00AM (closed on Sundays and on national holidays). SDS/Product information may not be available for the Emergency Service.)

Finland National Poison Information Center (09) 471 977 (direct) or (09) 4711 (exchange) (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)

France National Poisons Control Center ORFILA number (INRS): + 33 (0) 1 45 42 59 59 (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)

1.4. Emergency telephone number

Greece Poison Information Centre	(0030) 2107793777 (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)
Hungary National Emergency Phone Number	+36-80-201-199 (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)
Iceland Poison Center	(+354) 543 2222 (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)
Latvia Emergency medical aid	113
Latvia Poison and Drug Information Center	+371 67042473 (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)
Lithuania Neatidėliotina informacija apsinuodijus	+370 5 236 20 52 or +37068753378 (Hours of operation not provided. SDS/Product information may not be available for the Emergency Service.)
Malta Accident and Emergency Department	2545 4030 (Hours of operation not provided. SDS/Product information may not be available for the Emergency Service.)
Netherlands National Poisons Information Center (NVIC)	NVIC: +31 (0)88 755 8000 (Only for the purpose of informing medical personnel in cases of acute intoxications)
Norway Norwegian Poison Information Center	22 59 13 00 (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)
Portugal Poison Center	800 250 250 (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)
Romania Biroul RSI si Informare Toxicologica	021.318.36.06 (Available 8:00AM-3:00PM. SDS/Product information may not be available for the Emergency Service.)
Slovakia National Toxicological Information Center	+421 2 5477 4166 (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)
Spain Toxicology Information Service	+ 34 91 562 04 20 (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)
Sweden National Poison Information Center	112 - and ask for Poison Information (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)
Switzerland Tox Info Suisse	145 (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

The mixture has been assessed and/or tested for its physical, health and environmental hazards and the following classification applies.

Classification according to Regulation (EC) No 1272/2008 as amended

Physical hazards

Flammable liquids	Category 2	H225 - Highly flammable liquid and vapor.
-------------------	------------	---

Health hazards

Skin corrosion/irritation	Category 2	H315 - Causes skin irritation.
Serious eye damage/eye irritation	Category 1	H318 - Causes serious eye damage.
Skin sensitization	Category 1	H317 - May cause an allergic skin reaction.
Specific target organ toxicity - single exposure	Category 3 respiratory tract irritation	H335 - May cause respiratory irritation.

Environmental hazards

Hazardous to the aquatic environment, long-term aquatic hazard	Category 3	H412 - Harmful to aquatic life with long lasting effects.
--	------------	---

2.2. Label elements

Label according to Regulation (EC) No. 1272/2008 as amended

UFI:

Austria: NV90-2065-S00P-W143
Belgium: NV90-2065-S00P-W143
Bulgaria: NV90-2065-S00P-W143
Croatia: NV90-2065-S00P-W143
Cyprus: NV90-2065-S00P-W143
Czech Republic: NV90-2065-S00P-W143
Denmark: NV90-2065-S00P-W143
Estonia: NV90-2065-S00P-W143
EU: NV90-2065-S00P-W143
Finland: NV90-2065-S00P-W143
France: NV90-2065-S00P-W143
Germany: NV90-2065-S00P-W143
Greece: NV90-2065-S00P-W143
Hungary: NV90-2065-S00P-W143
Iceland: NV90-2065-S00P-W143
Ireland: NV90-2065-S00P-W143
Italy: NV90-2065-S00P-W143
Latvia: NV90-2065-S00P-W143
Lithuania: NV90-2065-S00P-W143
Luxembourg: NV90-2065-S00P-W143
Malta: NV90-2065-S00P-W143
Netherlands: NV90-2065-S00P-W143
Norway: NV90-2065-S00P-W143
Poland: NV90-2065-S00P-W143
Portugal: NV90-2065-S00P-W143
Romania: NV90-2065-S00P-W143
Slovakia: NV90-2065-S00P-W143
Slovenia: NV90-2065-S00P-W143
Spain: NV90-2065-S00P-W143
Sweden: NV90-2065-S00P-W143

Contains:

methacrylic acid; 2-methylpropenoic acid, methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate

Hazard pictograms



Signal word

Danger

Hazard statements

H225	Highly flammable liquid and vapor.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H335	May cause respiratory irritation.
H412	Harmful to aquatic life with long lasting effects.

Precautionary statements

Prevention

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233	Keep container tightly closed.
P235	Keep cool.
P240	Ground and bond container and receiving equipment.
P241	Use explosion-proof electrical/ventilating/lighting equipment.
P242	Use non-sparking tools.
P243	Take action to prevent static discharges.
P261	Avoid breathing mist/vapors.
P264	Wash thoroughly after handling.
P271	Use only outdoors or in a well-ventilated area.
P272	Contaminated work clothing should not be allowed out of the workplace.
P273	Avoid release to the environment.
P280	Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.

Response

P303 + P361 + P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P304 + P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310	Immediately call a POISON CENTER/doctor.
P333 + P313	If skin irritation or rash occurs: Get medical advice/attention.

P362 + P364
P370 + P378

Take off contaminated clothing and wash it before reuse.
In case of fire: Use appropriate media to extinguish.

Storage

P403 + P233
P403 + P235
P405

Store in a well-ventilated place. Keep container tightly closed.
Store in a well-ventilated place. Keep cool.
Store locked up.

Disposal

P501

Dispose of contents/container in accordance with local/regional/national/international regulations.

Supplemental label information

None.

2.3. Other hazards

This mixture does not contain substances assessed to be vPvB / PBT according to Regulation (EC) No 1907/2006, Annex XIII. The mixture does not contain any substances included in the list established in accordance with REACH Article 59(1) for having endocrine disrupting properties at a concentration equal to or greater than 0.1% by weight.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

General information

Chemical name	%	CAS-No. / EC No.	REACH Registration No.	Index No.	Notes
methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate	40 - 70	80-62-6 201-297-1	01-2119452498-28-0000	607-035-00-6	#
Classification: Flam. Liq. 2;H225, Skin Irrit. 2;H315, Skin Sens. 1;H317, STOT SE 3;H335					
Specific Concentration Limits: STOT SE 3;H335: C ≥ 10 %					
methacrylic acid; 2-methylpropenoic acid	3 - < 5	79-41-4 201-204-4	01-2119463884-26-0000	607-088-00-5	
Classification: Acute Tox. 4;H302;(ATE: 500 mg/kg bw), Acute Tox. 4;H312;(ATE: 1100 mg/kg bw), Acute Tox. 3;H331;(ATE: 7,1000000000000005 mg/l), Skin Corr. 1A;H314, Eye Dam. 1;H318, STOT SE 3;H335					
Specific Concentration Limits: STOT SE 3;H335: C ≥ 1 %					
zinc oxide	< 1	1314-13-2 215-222-5	-	030-013-00-7	
Classification: Aquatic Acute 1;H400, Aquatic Chronic 1;H410					
N,N-dimethyl-p-toluidine; [1] N,N-dimethyl-m-toluidine; [2] N,N-dimethyl-o-toluidine [3]	< 0,3	99-97-8 202-805-4	-	612-056-00-9	
Classification: Acute Tox. 3;H301;(ATE: 100 mg/kg bw), Acute Tox. 3;H311;(ATE: 300 mg/kg bw), Acute Tox. 3;H331;(ATE: 3 mg/l), Carc. 2;H351, STOT RE 2;H373, Aquatic Chronic 3;H412					
phosphoric acid ... %, orthophosphoric acid ... %	< 0,2	7664-38-2 231-633-2	-	015-011-00-6	#
Classification: Acute Tox. 4;H302;(ATE: 1530 mg/kg bw), Acute Tox. 2;H330;(ATE: 0,8445 mg/l), Skin Corr. 1B;H314, Eye Dam. 1;H318					
Specific Concentration Limits: Skin Corr. 1B;H314: C ≥ 25 %, Skin Irrit. 2;H315: 10 % ≤ C < 25 %, Eye Dam. 1;H314: C ≥ 25 %, Eye Irrit. 2;H319: 10 % ≤ C < 25 %					
Other components below reportable levels	30 - 60				

List of abbreviations and symbols that may be used above

ATE: Acute toxicity estimate.

M: M-factor

vPvB: very persistent and very bioaccumulative substance.

PBT: persistent, bioaccumulative and toxic substance.

#: This substance has been assigned Union workplace exposure limit(s).

All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

Composition comments

The full text for all H-statements is displayed in section 16.

SECTION 4: First aid measures

General information

Take off all contaminated clothing immediately. If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Wash contaminated clothing before reuse.

4.1. Description of first aid measures

Inhalation	Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a poison center or doctor/physician if you feel unwell.
Skin contact	Remove contaminated clothing immediately and wash skin with soap and water. In case of eczema or other skin disorders: Seek medical attention and take along these instructions. Wash contaminated clothing before reuse.
Eye contact	Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention immediately.
Ingestion	Rinse mouth. Get medical attention if symptoms occur.
4.2. Most important symptoms and effects, both acute and delayed	Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Permanent eye damage including blindness could result. May cause respiratory irritation. Skin irritation. May cause redness and pain. May cause an allergic skin reaction. Dermatitis. Rash.
4.3. Indication of any immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically. Thermal burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital. Keep victim under observation. Symptoms may be delayed.

SECTION 5: Firefighting measures

General fire hazards	Highly flammable liquid and vapor.
5.1. Extinguishing media	
Suitable extinguishing media	Water fog. Foam. Dry chemical powder. Carbon dioxide (CO ₂).
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.
5.2. Special hazards arising from the substance or mixture	Vapors may form explosive mixtures with air. Vapors may travel considerable distance to a source of ignition and flash back. During fire, gases hazardous to health may be formed.
5.3. Advice for firefighters	
Special protective equipment for firefighters	Self-contained breathing apparatus and full protective clothing must be worn in case of fire.
Special fire fighting procedures	In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do so without risk.
Specific methods	Use standard firefighting procedures and consider the hazards of other involved materials.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures	
For non-emergency personnel	Avoid breathing mist/vapors. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Do not touch or walk through spilled material.
For emergency responders	Keep unnecessary personnel away. Wear appropriate protective equipment and clothing during clean-up. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Ventilate closed spaces before entering them. Avoid breathing mist/vapors. Local authorities should be advised if significant spillages cannot be contained. Use personal protection recommended in Section 8 of the SDS.
6.2. Environmental precautions	Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground.
6.3. Methods and material for containment and cleaning up	Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Take precautionary measures against static discharge. Use only non-sparking tools. Prevent product from entering drains. Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Following product recovery, flush area with water. Small Spills: Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. Never return spills to original containers for re-use.
6.4. Reference to other sections	For personal protection, see section 8 of the SDS. For waste disposal, see section 13 of the SDS.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. When using do not smoke. Explosion-proof general and local exhaust ventilation. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Use non-sparking tools and explosion-proof equipment. Do not get this material in contact with eyes. Avoid breathing mist/vapors. Avoid contact with eyes, skin, and clothing. Wear appropriate personal protective equipment. Avoid release to the environment. Observe good industrial hygiene practices.

7.2. Conditions for safe storage, including any incompatibilities

Store locked up. Keep away from heat, sparks and open flame. Prevent electrostatic charge build-up by using common bonding and grounding techniques. Store in a cool, dry place out of direct sunlight. Store in tightly closed container. Store in a well-ventilated place. Keep in an area equipped with sprinklers. Store away from incompatible materials (see Section 10 of the SDS).

Directive 2012/18/EU on major accident hazards involving dangerous substances, as amended

ANNEX 1, PART 1 Categories of dangerous substances

Hazard categories in accordance with Regulation (EC) No 1272/2008

- P5a, b or c FLAMMABLE LIQUIDS (Lower-tier requirements = 50 tons; Upper-tier requirements = 200 tons)

7.3. Specific end use(s)

Observe industrial sector guidance on best practices.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

Austria. MAK List, OEL Ordinance (GwV), BGBl. II, no. 184/2001, as amended

Components	Type	Value	Form
methacrylic acid; 2-methylpropenoic acid (CAS 79-41-4)	MAK	70 mg/m3	
		20 ppm	
methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate (CAS 80-62-6)	Ceiling	420 mg/m3	
		100 ppm	
	MAK	210 mg/m3	
		50 ppm	
phosphoric acid ... %, orthophosphoric acid ... % (CAS 7664-38-2)	MAK	1 mg/m3	
	STEL	2 mg/m3	
zinc oxide (CAS 1314-13-2)	MAK	5 mg/m3	Fume and respirable dust.
	STEL	20 mg/m3	Inhalable fraction.
		10 mg/m3	Respirable fraction.

Belgium. OEL. Exposure Limit Values to Chemical Substances at Work, Code of Well-being at work, Book VI, Title 1 - Chemical agents, as amended

Components	Type	Value	Form
methacrylic acid; 2-methylpropenoic acid (CAS 79-41-4)	TWA	71 mg/m3	
		20 ppm	
methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate (CAS 80-62-6)	STEL	416 mg/m3	
		100 ppm	
	TWA	208 mg/m3	
		50 ppm	
Paraffin Wax (CAS 8002-74-2)	TWA	2 mg/m3	Fume.

Belgium. OEL. Exposure Limit Values to Chemical Substances at Work, Code of Well-being at work, Book VI, Title 1 - Chemical agents, as amended

Components	Type	Value	Form
phosphoric acid ... %, orthophosphoric acid ... % (CAS 7664-38-2)	STEL	2 mg/m3	
	TWA	1 mg/m3	
zinc oxide (CAS 1314-13-2)	STEL	10 mg/m3	Respirable fraction.
	TWA	2 mg/m3	Respirable fraction.

Bulgaria. OELs. Ordinance No 13 on protection of workers against risks of exposure to chemical agents at work, as amended

Components	Type	Value	
methacrylic acid; 2-methylpropenoic acid (CAS 79-41-4)	TWA	70 mg/m3	
methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate (CAS 80-62-6)	STEL	100 ppm	
	TWA	50 ppm	
phosphoric acid ... %, orthophosphoric acid ... % (CAS 7664-38-2)	STEL	2 mg/m3	
	TWA	1 mg/m3	
zinc oxide (CAS 1314-13-2)	STEL	10 mg/m3	
	TWA	5 mg/m3	

Croatia. OELs (GVI). Regulation on Protection of Workers against Exposure to Dangerous Chemicals at Work, OELs and Biological Limit Values, Annex I (NN 91/2018), as amended

Components	Type	Value	Form
methacrylic acid; 2-methylpropenoic acid (CAS 79-41-4)	MAC	72 mg/m3	
		20 ppm	
	STEL	143 mg/m3	
		40 ppm	
methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate (CAS 80-62-6)	MAC	50 ppm	
	STEL	100 ppm	
Paraffin Wax (CAS 8002-74-2)	MAC	2 mg/m3	Fume.
	STEL	6 mg/m3	Fume.
phosphoric acid ... %, orthophosphoric acid ... % (CAS 7664-38-2)	MAC	1 mg/m3	
	STEL	2 mg/m3	
zinc oxide (CAS 1314-13-2)	MAC	2 mg/m3	Respirable dust.
	STEL	10 mg/m3	Respirable dust.

Cyprus. OELs. Control of factory atmosphere and dangerous substances in factories regulation, PI 311/73, as amended

Components	Type	Value	Form
zinc oxide (CAS 1314-13-2)	TWA	5 mg/m3	Fume.

Cyprus. OELs. Occupational Exposure Limit Values of Chemicals at Work (Safety and Health at Work (Chem. Agents) Reg., Ann. 1, R.A.A. 268/2001, as amended)

Components	Type	Value	
methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate (CAS 80-62-6)	STEL	100 ppm	

Cyprus. OELs. Occupational Exposure Limit Values of Chemicals at Work (Safety and Health at Work (Chem. Agents) Reg., Ann. 1, R.A.A. 268/2001, as amended)

Components	Type	Value
	TWA	50 ppm
phosphoric acid ... %, orthophosphoric acid ... % (CAS 7664-38-2)	STEL	2 mg/m3
	TWA	1 mg/m3

Czech Republic. Occupational exposure limit values of chemicals at work (Decree on protection of health at work, 361/2007, Annex 2, Part A & Annex 3, Part A, as amended)

Components	Type	Value
methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate (CAS 80-62-6)	Ceiling	150 mg/m3
	TWA	50 mg/m3
N,N-dimethyl-p-toluidine; [1] N,N-dimethyl-m-toluidine; [2] N,N-dimethyl-o-toluidine [3] (CAS 99-97-8)	Ceiling	10 mg/m3
	TWA	5 mg/m3
phosphoric acid ... %, orthophosphoric acid ... % (CAS 7664-38-2)	Ceiling	2 mg/m3
	TWA	1 mg/m3
zinc oxide (CAS 1314-13-2)	Ceiling	5 mg/m3
	TWA	2 mg/m3

Denmark. Work Environment Authority. Exposure Limits for Substances & Materials, Annex 2

Components	Type	Value	Form
methacrylic acid; 2-methylpropenoic acid (CAS 79-41-4)	TLV	70 mg/m3	
		20 ppm	
methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate (CAS 80-62-6)	TLV	102 mg/m3	
		25 ppm	
Paraffin Wax (CAS 8002-74-2)	TLV	2 mg/m3	Fume.
phosphoric acid ... %, orthophosphoric acid ... % (CAS 7664-38-2)	TLV	1 mg/m3	
zinc oxide (CAS 1314-13-2)	TLV	4 mg/m3	

Estonia. OELs. Occupational Exposure Limits of Hazardous Substances (Regulation No. 105/2001, Annex), as amended

Components	Type	Value	Form
methacrylic acid; 2-methylpropenoic acid (CAS 79-41-4)	STEL	100 mg/m3	
		30 ppm	
	TWA	70 mg/m3	
		20 ppm	
methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate (CAS 80-62-6)	STEL	100 ppm	
	TWA	50 ppm	
Paraffin Wax (CAS 8002-74-2)	TWA	2 mg/m3	Vapor.

Estonia. OELs. Occupational Exposure Limits of Hazardous Substances (Regulation No. 105/2001, Annex), as amended

Components	Type	Value	Form
phosphoric acid ... %, orthophosphoric acid ... % (CAS 7664-38-2)	STEL	2 mg/m3	Vapor.
	TWA	1 mg/m3	Vapor.
zinc oxide (CAS 1314-13-2)	TWA	5 mg/m3	

Finland. HTP-arvot, App 3., Binding Limit Values, Social Affairs and Ministry of Health

Components	Type	Value	Form
methacrylic acid; 2-methylpropenoic acid (CAS 79-41-4)	TWA	71 mg/m3	
		20 ppm	
methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate (CAS 80-62-6)	STEL	210 mg/m3	
		50 ppm	
	TWA	42 mg/m3	
		10 ppm	
Paraffin Wax (CAS 8002-74-2)	TWA	1 mg/m3	Fume.
phosphoric acid ... %, orthophosphoric acid ... % (CAS 7664-38-2)	STEL	2 mg/m3	
	TWA	1 mg/m3	
zinc oxide (CAS 1314-13-2)	STEL	10 mg/m3	Fume.
	TWA	2 mg/m3	Fume.

France. OELs. Indicative Occupational Exposure Limits as Prescribed by Order of 30 June 2004, as amended

Components	Type	Value
phosphoric acid ... %, orthophosphoric acid ... % (CAS 7664-38-2)	VLE	2 mg/m3
		0,5 ppm
	VME	1 mg/m3
		0,2 ppm

France. OELs. Occupational Exposure Limits as Prescribed by Art. R.4412-149 of Labor Code, as amended

Components	Type	Value
methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate (CAS 80-62-6)	VLE	410 mg/m3
		100 ppm
	VME	205 mg/m3
		50 ppm

France. Threshold Limit Values (VLEP) for Occupational Exposure to Chemicals in France, INRS ED 984

Components	Type	Value	Form
methacrylic acid; 2-methylpropenoic acid (CAS 79-41-4)	VME	70 mg/m3	
Regulatory status: Indicative limit (VL)			
		20 ppm	
Regulatory status: Indicative limit (VL)			
methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate (CAS 80-62-6)	VLE	410 mg/m3	
Regulatory status: Regulatory binding (VRC)			

France. Threshold Limit Values (VLEP) for Occupational Exposure to Chemicals in France, INRS ED 984

Components	Type	Value	Form
Regulatory status: Regulatory binding (VRC)		100 ppm	
VME		205 mg/m3	
Regulatory status: Regulatory binding (VRC)		50 ppm	
Regulatory status: Regulatory binding (VRC)			
Paraffin Wax (CAS 8002-74-2)	VME	2 mg/m3	Fume.
Regulatory status: Indicative limit (VL)			
phosphoric acid ... %, orthophosphoric acid ... % (CAS 7664-38-2)	VLE	2 mg/m3	
Regulatory status: Regulatory indicative (VRI)			
		0,5 ppm	
Regulatory status: Regulatory indicative (VRI)			
VME		1 mg/m3	
Regulatory status: Regulatory indicative (VRI)			
		0,2 ppm	
Regulatory status: Regulatory indicative (VRI)			
zinc oxide (CAS 1314-13-2)	VME	5 mg/m3	Fume.
Regulatory status: Indicative limit (VL)			
		10 mg/m3	Dust.
Regulatory status: Indicative limit (VL)			

Germany. DFG MAK List (advisory OELs). Commission for the Investigation of Health Hazards of Chemical Compounds in the Work Area (DFG), as updated

Components	Type	Value	Form
methacrylic acid; 2-methylpropenoic acid (CAS 79-41-4)	TWA	180 mg/m3	
		50 ppm	
methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate (CAS 80-62-6)	TWA	210 mg/m3	
		50 ppm	
phosphoric acid ... %, orthophosphoric acid ... % (CAS 7664-38-2)	TWA	2 mg/m3	Inhalable fraction.

Germany. TRGS 900, Limit Values in the Ambient Air at the Workplace

Components	Type	Value	Form
methacrylic acid; 2-methylpropenoic acid (CAS 79-41-4)	AGW	180 mg/m3	
		50 ppm	
methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate (CAS 80-62-6)	AGW	210 mg/m3	
		50 ppm	
phosphoric acid ... %, orthophosphoric acid ... % (CAS 7664-38-2)	AGW	2 mg/m3	Inhalable fraction.
zinc oxide (CAS 1314-13-2)	AGW	10 mg/m3	Inhalable fraction.
		1,25 mg/m3	Respirable fraction.

Greece. OELs, Presidential Decree No. 307/1986, as amended

Components	Type	Value	Form
methacrylic acid; 2-methylpropenoic acid (CAS 79-41-4)	STEL	140 mg/m3	
		40 ppm	
	TWA	70 mg/m3 20 ppm	
methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate (CAS 80-62-6)	STEL	100 ppm	
	TWA	50 ppm	
Paraffin Wax (CAS 8002-74-2)	STEL	6 mg/m3	Fume.
	TWA	2 mg/m3	Fume.
phosphoric acid ... %, orthophosphoric acid ... % (CAS 7664-38-2)	STEL	3 mg/m3	
	TWA	1 mg/m3	
zinc oxide (CAS 1314-13-2)	STEL	10 mg/m3	Fume.
	TWA	5 mg/m3	Fume.

Hungary. OELs. Decree on protection of workers exposed to chemical agents (5/2020. (II.6)), Annex 1&2, as amended

Components	Type	Value	Form
methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate (CAS 80-62-6)	STEL	415 mg/m3	
	TWA	208 mg/m3	
phosphoric acid ... %, orthophosphoric acid ... % (CAS 7664-38-2)	STEL	2 mg/m3	
	TWA	1 mg/m3	
zinc oxide (CAS 1314-13-2)	TWA	5 mg/m3	Fume.
		5 mg/m3	Dust.

Iceland. OELs. Regulation 390/2009 on Pollution Limits and Measures to Reduce Pollution at the Workplace, as amended

Components	Type	Value	Form
methacrylic acid; 2-methylpropenoic acid (CAS 79-41-4)	TWA	70 mg/m3	
		20 ppm	
methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate (CAS 80-62-6)	STEL	100 ppm	
	TWA	50 ppm	
Paraffin Wax (CAS 8002-74-2)	TWA	2 mg/m3	Fume.
phosphoric acid ... %, orthophosphoric acid ... % (CAS 7664-38-2)	STEL	2 mg/m3	
	TWA	1 mg/m3	
zinc oxide (CAS 1314-13-2)	TWA	4 mg/m3	Fume.

Ireland. OELVs, Schedules 1 & 2, Code of Practice for Chemical Agents and Carcinogens Regulations

Components	Type	Value	Form
methacrylic acid; 2-methylpropenoic acid (CAS 79-41-4)	STEL	140 mg/m3	
		40 ppm	

Ireland. OELVs, Schedules 1 & 2, Code of Practice for Chemical Agents and Carcinogens Regulations

Components	Type	Value	Form
methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate (CAS 80-62-6)	TWA	70 mg/m3	
		20 ppm	
	STEL	100 ppm	
Paraffin Wax (CAS 8002-74-2)	TWA	50 ppm	
	STEL	6 mg/m3	Fume.
phosphoric acid ... %, orthophosphoric acid ... % (CAS 7664-38-2)	TWA	2 mg/m3	Fume.
	STEL	2 mg/m3	
zinc oxide (CAS 1314-13-2)	TWA	1 mg/m3	
	STEL	10 mg/m3	Respirable fraction and fume.
	TWA	2 mg/m3	Respirable fraction and fume.

Italy. OELs (Legislative Decree n.81, 9 April 2008), as amended

Components	Type	Value	Form
methacrylic acid; 2-methylpropenoic acid (CAS 79-41-4)	TWA	20 ppm	
	STEL	100 ppm	
methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate (CAS 80-62-6)	TWA	50 ppm	
	TWA	2 mg/m3	Fume.
phosphoric acid ... %, orthophosphoric acid ... % (CAS 7664-38-2)	STEL	2 mg/m3	
	TWA	1 mg/m3	
zinc oxide (CAS 1314-13-2)	STEL	10 mg/m3	Respirable fraction.
	TWA	2 mg/m3	Respirable fraction.

Latvia. OELs. Occupational Exposure Limits of Chemical Substances at Workplace (Reg. No. 325/ 2007, L.V. 80, Annex 1), as amended

Components	Type	Value
methacrylic acid; 2-methylpropenoic acid (CAS 79-41-4)	TWA	10 mg/m3
	TWA	10 mg/m3
methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate (CAS 80-62-6)	STEL	2 mg/m3
	TWA	1 mg/m3
zinc oxide (CAS 1314-13-2)	TWA	0,5 mg/m3

Lithuania. OELs. Occupational Exposure Limit Values for Chemical Substances (Hygiene Norm HN 23:2011; Order No. V-824/A1-389), as amended

Components	Type	Value
methacrylic acid; 2-methylpropenoic acid (CAS 79-41-4)	STEL	100 mg/m3
		30 ppm
	TWA	70 mg/m3

Lithuania. OELs. Occupational Exposure Limit Values for Chemical Substances (Hygiene Norm HN 23:2011; Order No. V-824/A1-389), as amended

Components	Type	Value
methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate (CAS 80-62-6)		20 ppm
	STEL	416 mg/m3
		100 ppm
phosphoric acid ... %, orthophosphoric acid ... % (CAS 7664-38-2)	TWA	208 mg/m3
		50 ppm
	STEL	2 mg/m3
zinc oxide (CAS 1314-13-2)	TWA	1 mg/m3
	TWA	5 mg/m3

Luxembourg. OELs. Binding Occupational Exposure Limit Values (Annex I), G.D.R. of 14 November 2016, OJ Memorial A, n ° 235/2016, as amended

Components	Type	Value
methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate (CAS 80-62-6)		100 ppm
	STEL	
	TWA	50 ppm
phosphoric acid ... %, orthophosphoric acid ... % (CAS 7664-38-2)	STEL	2 mg/m3
	TWA	1 mg/m3

Malta. OELs. Protection of Health and Safety of Workers from Risks related to Chemical Agents at Work (L.N 227/2003 Schedules I and V), as amended

Components	Type	Value
methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate (CAS 80-62-6)		100 ppm
	STEL	
	TWA	50 ppm
phosphoric acid ... %, orthophosphoric acid ... % (CAS 7664-38-2)	STEL	2 mg/m3
	TWA	1 mg/m3

Netherlands. OELs per Annex XIII of Working Conditions Regulation (Staatscourant no. 252, 29 December 2006), as amended

Components	Type	Value
methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate (CAS 80-62-6)		410 mg/m3
	STEL	
	TWA	205 mg/m3
phosphoric acid ... %, orthophosphoric acid ... % (CAS 7664-38-2)	STEL	2 mg/m3
	TWA	1 mg/m3

Norway. Regulation No. 1358 on Measures and Limit Values for Physical and Chemical Factors in Work Environment and Infection Groups for Biological Factors, as amended

Components	Type	Value	Form
methacrylic acid; 2-methylpropenoic acid (CAS 79-41-4)	TLV	70 mg/m3	
		20 ppm	

Norway. Regulation No. 1358 on Measures and Limit Values for Physical and Chemical Factors in Work Environment and Infection Groups for Biological Factors, as amended

Components	Type	Value	Form
methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate (CAS 80-62-6)	STEL	400 mg/m3	
		100 ppm	
	TLV	100 mg/m3	
Paraffin Wax (CAS 8002-74-2)	TLV	25 ppm	
		2 mg/m3	Fume.
phosphoric acid ... %, orthophosphoric acid ... % (CAS 7664-38-2)	TLV	1 mg/m3	
zinc oxide (CAS 1314-13-2)	TLV	5 mg/m3	Respirable dust.
		5 mg/m3	Dust.
		10 mg/m3	Total dust.

Poland. Maximum permissible concentrations and intensities of harmful factors in the work environment (Dz.U.Poz. 1286/2018, Annex 1)

Components	Type	Value	Form
methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate (CAS 80-62-6)	STEL	300 mg/m3	
	TWA	100 mg/m3	
Paraffin Wax (CAS 8002-74-2)	TWA	2 mg/m3	Inhalable fraction.
phosphoric acid ... %, orthophosphoric acid ... % (CAS 7664-38-2)	STEL	2 mg/m3	
	TWA	1 mg/m3	
zinc oxide (CAS 1314-13-2)	STEL	10 mg/m3	Inhalable fraction.
	TWA	5 mg/m3	Inhalable fraction.

Portugal. Decree-Law No. 24/2012, Occupational Exposure Limit Values, Annex II, as amended

Components	Type	Value
phosphoric acid ... %, orthophosphoric acid ... % (CAS 7664-38-2)	STEL	2 mg/m3
	TWA	1 mg/m3

Portugal. VLEs. Norm on occupational exposure to chemical agents (NP 1796-2014)

Components	Type	Value	Form
methacrylic acid; 2-methylpropenoic acid (CAS 79-41-4)	TWA	20 ppm	
	STEL	100 ppm	
methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate (CAS 80-62-6)	TWA	50 ppm	
	TWA	2 mg/m3	Fume.
phosphoric acid ... %, orthophosphoric acid ... % (CAS 7664-38-2)	STEL	3 mg/m3	
	TWA	1 mg/m3	
zinc oxide (CAS 1314-13-2)	STEL	10 mg/m3	Respirable fraction.
	TWA	2 mg/m3	Respirable fraction.

Romania. OELs. Limit Values of Chemical Agents at Workplace (Regulation 1.218/2006, M.O 845, Annex 1, 3&4, as amended)

Components	Type	Value	Form
methacrylic acid; 2-methylpropenoic acid (CAS 79-41-4)	STEL	45 mg/m3	
		13 ppm	
	TWA	30 mg/m3 8,5 ppm	
methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate (CAS 80-62-6)	STEL	410 mg/m3	
		100 ppm	
	TWA	205 mg/m3 50 ppm	
Paraffin Wax (CAS 8002-74-2)	STEL	6 mg/m3	Fume.
	TWA	2 mg/m3	Fume.
phosphoric acid ... %, orthophosphoric acid ... % (CAS 7664-38-2)	STEL	2 mg/m3	
	TWA	1 mg/m3	
zinc oxide (CAS 1314-13-2)	STEL	10 mg/m3	Fume.
	TWA	5 mg/m3	Fume.

Slovakia. OELs. Maximum permissible exposure limits for chemical factors in workplace air (Regulation No 355/2006, Annex 1, Table 1, as amended)

Components	Type	Value	Form
methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate (CAS 80-62-6)	STEL	100 ppm	
	TWA	50 ppm	
Paraffin Wax (CAS 8002-74-2)	STEL	6 mg/m3	Fume.
	TWA	2 mg/m3	Fume.
phosphoric acid ... %, orthophosphoric acid ... % (CAS 7664-38-2)	STEL	2 mg/m3	
	TWA	1 mg/m3	
zinc oxide (CAS 1314-13-2)	STEL	1 mg/m3	Respirable fume.
	TWA	1 mg/m3	Respirable fume.

Slovenia. OELs. Occupational Exposure Limits of Chemicals at Workplace (Reg. on Protection of Workers from Risks due to Exp. to Chemicals at Work, Annex I), as amended

Components	Type	Value	Form
methacrylic acid; 2-methylpropenoic acid (CAS 79-41-4)	TWA	180 mg/m3	
		50 ppm	
methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate (CAS 80-62-6)	TWA	210 mg/m3	
		50 ppm	
phosphoric acid ... %, orthophosphoric acid ... % (CAS 7664-38-2)	TWA	1 mg/m3	
zinc oxide (CAS 1314-13-2)	TWA	10 mg/m3	Inhalable fraction.
		1,25 mg/m3	Respirable fraction.

Spain. OELs. INSST, Límites de Exposición Profesional Para Agentes Químicos, Table 1-Valores Límites Ambientales (VLAs)

Components	Type	Value	Form
methacrylic acid; 2-methylpropenoic acid (CAS 79-41-4)	TWA	72 mg/m3	
		20 ppm	
methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate (CAS 80-62-6)	STEL	100 ppm	
	TWA	50 ppm	
Paraffin Wax (CAS 8002-74-2)	TWA	2 mg/m3	Fume.
phosphoric acid ... %, orthophosphoric acid ... % (CAS 7664-38-2)	STEL	2 mg/m3	
	TWA	1 mg/m3	
zinc oxide (CAS 1314-13-2)	STEL	10 mg/m3	Respirable fraction.
	TWA	2 mg/m3	Respirable fraction.

Sweden. OELs (Annex 1). Work Environment Authority (AV), Occupational Exposure Limit Values (AFS 2018:1), as amended

Components	Type	Value	Form
methacrylic acid; 2-methylpropenoic acid (CAS 79-41-4)	STEL	100 mg/m3	
		30 ppm	
	TWA	70 mg/m3	
		20 ppm	
methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate (CAS 80-62-6)	Ceiling	400 mg/m3	
		100 ppm	
	TWA	200 mg/m3	
		50 ppm	
phosphoric acid ... %, orthophosphoric acid ... % (CAS 7664-38-2)	Ceiling	2 mg/m3	
	TWA	1 mg/m3	
zinc oxide (CAS 1314-13-2)	TWA	5 mg/m3	Total dust.

Switzerland. SUVA Grenzwerte am Arbeitsplatz: Aktuelle MAK-Werte

Components	Type	Value	Form
methacrylic acid; 2-methylpropenoic acid (CAS 79-41-4)	STEL	360 mg/m3	
		100 ppm	
	TWA	180 mg/m3	
		50 ppm	
methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate (CAS 80-62-6)	STEL	420 mg/m3	
		100 ppm	
	TWA	210 mg/m3	
		50 ppm	
Paraffin Wax (CAS 8002-74-2)	TWA	2 mg/m3	Respirable fume.

Switzerland. SUVA Grenzwerte am Arbeitsplatz: Aktuelle MAK-Werte

Components	Type	Value	Form
phosphoric acid ... %, orthophosphoric acid ... % (CAS 7664-38-2)	STEL	4 mg/m3	Inhalable fraction.
	TWA	2 mg/m3	Inhalable fraction.
zinc oxide (CAS 1314-13-2)	STEL	3 mg/m3	Respirable fume.
	TWA	3 mg/m3	Respirable fume.

UK. OELs. Workplace Exposure Limits (WELs) (EH40/2005 (Fourth Edition 2020)), Table 1

Components	Type	Value	Form
methacrylic acid; 2-methylpropenoic acid (CAS 79-41-4)	STEL	143 mg/m3	
		40 ppm	
	TWA	72 mg/m3	
		20 ppm	
methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate (CAS 80-62-6)	STEL	416 mg/m3	
		100 ppm	
	TWA	208 mg/m3	
		50 ppm	
Paraffin Wax (CAS 8002-74-2)	STEL	6 mg/m3	Fume.
	TWA	2 mg/m3	Fume.
phosphoric acid ... %, orthophosphoric acid ... % (CAS 7664-38-2)	STEL	2 mg/m3	
	TWA	1 mg/m3	
zinc oxide (CAS 1314-13-2)	TWA	4 mg/m3	Respirable dust.
		10 mg/m3	Inhalable dust.

EU. Indicative Exposure Limit Values in Directives 91/322/EEC, 2000/39/EC, 2006/15/EC, 2009/161/EU, 2017/164/EU

Components	Type	Value
methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate (CAS 80-62-6)	STEL	100 ppm
	TWA	50 ppm
phosphoric acid ... %, orthophosphoric acid ... % (CAS 7664-38-2)	STEL	2 mg/m3
	TWA	1 mg/m3

Biological limit values

No biological exposure limits noted for the ingredient(s).

Recommended monitoring procedures

Follow standard monitoring procedures.

Derived no effect levels (DNELs)

Not available.

Predicted no effect concentrations (PNECs)

Not available.

Exposure guidelines

Occupational Exposure Limits are not relevant to the current physical form of the product.

Croatia ELVs: Skin designation

methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate (CAS 80-62-6)

Can be absorbed through the skin.

Denmark GV: Skin designation

methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate (CAS 80-62-6)

Can be absorbed through the skin.

Germany DFG MAK (advisory): Skin designation

N,N-dimethyl-p-toluidine; [1] N,N-dimethyl-m-toluidine; [2] Can be absorbed through the skin.
N,N-dimethyl-o-toluidine [3] (CAS 99-97-8)

Hungary OELs: Skin designation

methyl methacrylate; methyl 2-methylprop-2-enoate; Can be absorbed through the skin.
methyl 2-methylpropenoate (CAS 80-62-6)

Iceland OELs: Skin designation

methyl methacrylate; methyl 2-methylprop-2-enoate; Can be absorbed through the skin.
methyl 2-methylpropenoate (CAS 80-62-6)

Slovenia. OELs. Regulations concerning protection of workers against risks due to exposure to chemicals while working (Official Gazette of the Republic of Slovenia)

methacrylic acid; 2-methylpropenoic acid (CAS 79-41-4) Can be absorbed through the skin.

8.2. Exposure controls**Appropriate engineering controls**

Explosion-proof general and local exhaust ventilation. Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station and safety shower.

Individual protection measures, such as personal protective equipment**General information**

Use personal protective equipment as required. Personal protection equipment should be chosen according to the CEN standards and in discussion with the supplier of the personal protective equipment.

Eye/face protection

Chemical respirator with organic vapor cartridge and full facepiece.

Skin protection**- Hand protection**

Wear appropriate chemical resistant gloves.

- Other

Wear appropriate chemical resistant clothing.

Respiratory protection

Chemical respirator with organic vapor cartridge and full facepiece.

Thermal hazards

Wear appropriate thermal protective clothing, when necessary.

Hygiene measures

When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Contaminated work clothing should not be allowed out of the workplace.

Environmental exposure controls

Inform appropriate managerial or supervisory personnel of all environmental releases. Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. Fume scrubbers, filters or engineering modifications to the process equipment may be necessary to reduce emissions to acceptable levels.

SECTION 9: Physical and chemical properties**9.1. Information on basic physical and chemical properties**

Physical state	Liquid.
Form	Liquid. Paste.
Color	Off-white
Odor	Fragrant
Melting point/freezing point	-54,4 °F (-48 °C) estimated
Boiling point or initial boiling point and boiling range	212,9 °F (100,5 °C) estimated
Flammability	Not applicable.
Upper/lower flammability or explosive limits	
Explosive limit - lower (%)	2,1 % estimated
Explosive limit - upper (%)	8,2 % estimated
Flash point	50,0 °F (10,0 °C) estimated
Auto-ignition temperature	815 °F (435 °C) estimated
Decomposition temperature	Not available.
pH	Not available.
Kinematic viscosity	Not available.
Solubility	
Solubility (water)	Not available.
Partition coefficient (n-octanol/water) (log value)	Not available.

Vapor pressure	51,33 hPa estimated
Density and/or relative density	
Density	0,94 g/cm3 estimated
Vapor density	Not available.
Particle characteristics	Not available.

9.2. Other information

9.2.1. Information with regard to physical hazard classes No relevant additional information available.

9.2.2. Other safety characteristics

Specific gravity	0,94 estimated
VOC	63,94 % estimated <50 g/l Mixed

SECTION 10: Stability and reactivity

10.1. Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
10.2. Chemical stability	Material is stable under normal conditions.
10.3. Possibility of hazardous reactions	No dangerous reaction known under conditions of normal use.
10.4. Conditions to avoid	Avoid heat, sparks, open flames and other ignition sources. Avoid temperatures exceeding the flash point. Contact with incompatible materials.
10.5. Incompatible materials	Strong oxidizing agents. Nitrates. Peroxides.
10.6. Hazardous decomposition products	No hazardous decomposition products are known.

SECTION 11: Toxicological information

General information Occupational exposure to the substance or mixture may cause adverse effects.

Information on likely routes of exposure

Inhalation	May cause irritation to the respiratory system.
Skin contact	Causes skin irritation. May cause an allergic skin reaction.
Eye contact	Causes serious eye damage.
Ingestion	May cause discomfort if swallowed. However, ingestion is not likely to be a primary route of occupational exposure.
Symptoms	Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Permanent eye damage including blindness could result. May cause respiratory irritation. Skin irritation. May cause redness and pain. May cause an allergic skin reaction. Dermatitis. Rash.

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity Not known.

Components	Species	Test Results
methacrylic acid; 2-methylpropenoic acid (CAS 79-41-4)		
Acute		
Inhalation		
LC50	Rat	7,1000000000000005 mg/l, 4 Hours
methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate (CAS 80-62-6)		
Acute		
Oral		
LD50	Rat	7800 mg/kg
phosphoric acid ... %, orthophosphoric acid ... % (CAS 7664-38-2)		
Acute		
Dermal		
LD50	Rabbit	2740 mg/kg
Inhalation		
LC50	Rabbit	1,6890000000000001 mg/l, 1 Hours
Oral		
LD50	Rat	1530 mg/kg

Components	Species	Test Results
zinc oxide (CAS 1314-13-2)		
Acute		
Inhalation		
LC50	Mouse	> 5,7000000000000002 mg/l, 4 Hours
Oral		
LD50	Rat	> 5 g/kg
Skin corrosion/irritation	Causes skin irritation.	
Serious eye damage/eye irritation	Causes serious eye damage.	
Respiratory sensitization	Not a respiratory sensitizer.	
Skin sensitization	May cause an allergic skin reaction.	
Germ cell mutagenicity	Due to partial or complete lack of data the classification is not possible.	
Carcinogenicity	Risk of cancer cannot be excluded with prolonged exposure.	
IARC Monographs. Overall Evaluation of Carcinogenicity		
methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate (CAS 80-62-6)		3 Not classifiable as to carcinogenicity to humans.
N,N-dimethyl-p-toluidine; [1] N,N-dimethyl-m-toluidine; [2] N,N-dimethyl-o-toluidine [3] (CAS 99-97-8)		2B Possibly carcinogenic to humans.
Reproductive toxicity	Due to partial or complete lack of data the classification is not possible.	
Specific target organ toxicity - single exposure	May cause respiratory irritation.	
Specific target organ toxicity - repeated exposure	Due to partial or complete lack of data the classification is not possible.	
Aspiration hazard	Due to partial or complete lack of data the classification is not possible.	
Mixture versus substance information	No information available.	
11.2. Information on other hazards		
Endocrine disrupting properties	This mixture does not contain any substances having endocrine disrupting properties with respect to human health as assessed in accordance with the criteria set out in Regulations (EC) No 1907/2006, (EU) No 2017/2100 and (EU) 2018/605, at a concentration equal to or greater than 0.1% by weight.	
Other information	Not available.	
SECTION 12: Ecological information		
12.1. Toxicity	Harmful to aquatic life with long lasting effects. Based on available data, the classification criteria are not met for hazardous to the aquatic environment, acute hazard.	
12.2. Persistence and degradability	No data is available on the degradability of any ingredients in the mixture.	
12.3. Bioaccumulative potential		
Partition coefficient n-octanol/water (log Kow)		
methacrylic acid; 2-methylpropenoic acid	0,93	
methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate	1,38	
Bioconcentration factor (BCF)	Not available.	
12.4. Mobility in soil	No data available.	
12.5. Results of PBT and vPvB assessment	This mixture does not contain substances assessed to be vPvB / PBT according to Regulation (EC) No 1907/2006, Annex XIII.	
12.6. Endocrine disrupting properties	This mixture does not contain any substances having endocrine disrupting properties with respect to the environment as assessed in accordance with the criteria set out in Regulations (EC) No 1907/2006, (EU) No 2017/2100 and (EU) 2018/605, at a concentration equal to or greater than 0.1% by weight.	
12.7. Other adverse effects	The product contains volatile organic compounds which have a photochemical ozone creation potential.	
12.8. Additional information		
Estonia Dangerous substances in soil Data		
phosphoric acid ... %, orthophosphoric acid ... % (CAS 7664-38-2)	Chemical pesticides (As the total sum of the active substances) 0,5 MG/KG	

zinc oxide (CAS 1314-13-2)

Chemical pesticides (As the total sum of the active substances) 20
MG/KG

Chemical pesticides (As the total sum of the active substances) 5
MG/KG

Zinc (Zn) 1000 MG/KG

Zinc (Zn) 200 MG/KG

Zinc (Zn) 500 MG/KG

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Residual waste	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).
Contaminated packaging	Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.
EU waste code	The Waste code should be assigned in discussion between the user, the producer and the waste disposal company.
Disposal methods/information	Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international regulations.
Special precautions	Dispose in accordance with all applicable regulations.

SECTION 14: Transport information

ADR

14.1. UN number	UN1133
14.2. UN proper shipping name	ADHESIVES containing flammable liquid
14.3. Transport hazard class(es)	
Class	3
Subsidiary risk	-
Label(s)	3
Hazard No. (ADR)	30
Tunnel restriction code	D/E
14.4. Packing group	III
14.5. Environmental hazards	No.
14.6. Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.

RID

14.1. UN number	UN1133
14.2. UN proper shipping name	ADHESIVES containing flammable liquid
14.3. Transport hazard class(es)	
Class	3
Subsidiary risk	-
Label(s)	3
14.4. Packing group	III
14.5. Environmental hazards	No.
14.6. Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.

ADN

14.1. UN number	UN1133
14.2. UN proper shipping name	ADHESIVES containing flammable liquid
14.3. Transport hazard class(es)	
Class	3
Subsidiary risk	-
Label(s)	3
14.4. Packing group	III
14.5. Environmental hazards	No.
14.6. Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.

IATA

14.1. UN number	UN1133
------------------------	--------

14.2. UN proper shipping name	Adhesives containing flammable liquid, Limited Quantity
14.3. Transport hazard class(es)	
Class	3
Subsidiary risk	-
14.4. Packing group	III
14.5. Environmental hazards	No.
ERG Code	3L
14.6. Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
Other information	
Passenger and cargo aircraft	Allowed with restrictions.
Cargo aircraft only	Allowed with restrictions.

IMDG

14.1. UN number	UN1133
14.2. UN proper shipping name	ADHESIVES containing flammable liquid, Limited Quantity
14.3. Transport hazard class(es)	
Class	3
Subsidiary risk	-
14.4. Packing group	III
14.5. Environmental hazards	
Marine pollutant	No.
EmS	F-E, S-D
14.6. Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.

14.7. Maritime transport in bulk according to IMO instruments Not established.


ADN; ADR; RID



IATA



IMDG



SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulations

Regulation (EC) No. 1005/2009 on substances that deplete the ozone layer, Annex I and II, as amended

Not listed.

Regulation (EU) 2019/1021 On persistent organic pollutants (recast), as amended

Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 1 as amended

Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 2 as amended

Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 3 as amended

Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex V as amended

Not listed.

Regulation (EC) No. 166/2006 Annex II Pollutant Release and Transfer Registry, as amended

zinc oxide (CAS 1314-13-2)

Regulation (EC) No. 1907/2006, REACH Article 59(10) Candidate List as currently published by ECHA

Not listed.

UFI:

Austria: NV90-2065-S00P-W143
Belgium: NV90-2065-S00P-W143
Bulgaria: NV90-2065-S00P-W143
Croatia: NV90-2065-S00P-W143
Cyprus: NV90-2065-S00P-W143
Czech Republic: NV90-2065-S00P-W143
Denmark: NV90-2065-S00P-W143
Estonia: NV90-2065-S00P-W143
EU: NV90-2065-S00P-W143
Finland: NV90-2065-S00P-W143
France: NV90-2065-S00P-W143
Germany: NV90-2065-S00P-W143
Greece: NV90-2065-S00P-W143
Hungary: NV90-2065-S00P-W143
Iceland: NV90-2065-S00P-W143
Ireland: NV90-2065-S00P-W143
Italy: NV90-2065-S00P-W143
Latvia: NV90-2065-S00P-W143
Lithuania: NV90-2065-S00P-W143
Luxembourg: NV90-2065-S00P-W143
Malta: NV90-2065-S00P-W143
Netherlands: NV90-2065-S00P-W143
Norway: NV90-2065-S00P-W143
Poland: NV90-2065-S00P-W143
Portugal: NV90-2065-S00P-W143
Romania: NV90-2065-S00P-W143
Slovakia: NV90-2065-S00P-W143
Slovenia: NV90-2065-S00P-W143
Spain: NV90-2065-S00P-W143
Sweden: NV90-2065-S00P-W143

Authorizations

Regulation (EC) No. 1907/2006, REACH Annex XIV Substances subject to authorization, as amended

Not listed.

Restrictions on use

Regulation (EC) No. 1907/2006, REACH Annex XVII Substances subject to restriction on marketing and use, as amended

- Conditions of restriction given for the associated entry number should be considered

methacrylic acid; 2-methylpropenoic acid (CAS 79-41-4) 75
phosphoric acid ... %, orthophosphoric acid ... % 75
(CAS 7664-38-2)

Directive 2004/37/EC: on the protection of workers from the risks related to exposure to carcinogens and mutagens at work, as amended

Not listed.

Other EU regulations

Directive 2012/18/EU on major accident hazards involving dangerous substances, as amended

ANNEX 1, PART 1 Categories of dangerous substances
Hazard categories in accordance with Regulation (EC) No 1272/2008
- P5a, b or c FLAMMABLE LIQUIDS

Other regulations	The product is classified and labelled in accordance with Regulation (EC) 1272/2008 (CLP Regulation) as amended. This Safety Data Sheet complies with the requirements of Regulation (EC) No 1907/2006, as amended.	
National regulations	Young people under 18 years old are not allowed to work with this product according to EU Directive 94/33/EC on the protection of young people at work, as amended. Follow national regulation for work with chemical agents in accordance with Directive 98/24/EC, as amended.	
Contains a substance which is included on the TRGS 905 list of carcinogenic, germ cell mutagenic and reproductive toxic substances	zinc oxide (CAS 1314-13-2)	Anorganische Faserstäube, soweit nicht erwähnt (ausgenommen Gipsfasern und Wollastonitfasern)

France regulations

France INRS Table of Occupational Diseases

methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate (CAS 80-62-6)	Affections provoquées par le méthacrylate de méthyle 82
---	---

Product registration number

Austria	UFI: NV90-2065-S00P-W143
Belgium	UFI: NV90-2065-S00P-W143
Czech Republic	UFI: NV90-2065-S00P-W143
Denmark	UFI: NV90-2065-S00P-W143
European Union	UFI: NV90-2065-S00P-W143
Finland	UFI: NV90-2065-S00P-W143
France	UFI: NV90-2065-S00P-W143
Germany	UFI: NV90-2065-S00P-W143
Greece	UFI: NV90-2065-S00P-W143
Hungary	UFI: NV90-2065-S00P-W143
Italy	UFI: NV90-2065-S00P-W143
Netherlands	UFI: NV90-2065-S00P-W143
Norway	UFI: NV90-2065-S00P-W143
Poland	UFI: NV90-2065-S00P-W143
Portugal	UFI: NV90-2065-S00P-W143
Slovakia	UFI: NV90-2065-S00P-W143
Slovenia	UFI: NV90-2065-S00P-W143
Spain	UFI: NV90-2065-S00P-W143
Sweden	UFI: NV90-2065-S00P-W143
Switzerland	UFI: NV90-2065-S00P-W143

15.2. Chemical safety assessment

No Chemical Safety Assessment has been carried out.

SECTION 16: Other information

List of abbreviations

ADN: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways.
 ADR: Agreement concerning the International Carriage of Dangerous Goods by Road.
 AGW: Occupational threshold limit value (Arbeitsplatzgrenzwert – Germany).
 CAS: Chemical Abstract Service.
 CEN: European Committee for Standardization.
 IATA: International Air Transport Association.
 IBC Code: International Code for the Construction and Equipment of Ships Carrying Dangerous Chemicals in Bulk.
 IMDG: International Maritime Dangerous Goods.
 MAC: Maximum Allowed Concentration.
 MARPOL: International Convention for the Prevention of Pollution from Ships.
 PBT: Persistent, bioaccumulative and toxic.
 RID: Regulations concerning the International Carriage of Dangerous Goods by Rail.
 STEL: Short term exposure limit.
 TLV: Threshold Limit Value.
 TWA: Time Weighted Average.
 VLE: Exposure Limit Value.
 VME: Exposure Average Value.
 vPvB: Very persistent and very bioaccumulative.

References

Not available.

Information on evaluation method leading to the classification of mixture

The classification for health and environmental hazards is derived by a combination of calculation methods and test data, if available.

**Full text of any statements,
which are not written out in full
under sections 2 to 15**

H225 Highly flammable liquid and vapor.
H301 Toxic if swallowed.
H302 Harmful if swallowed.
H311 Toxic in contact with skin.
H312 Harmful in contact with skin.
H314 Causes severe skin burns and eye damage.
H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H318 Causes serious eye damage.
H330 Fatal if inhaled.
H331 Toxic if inhaled.
H335 May cause respiratory irritation.
H351 Suspected of causing cancer.
H373 May cause damage to organs through prolonged or repeated exposure.
H400 Very toxic to aquatic life.
H410 Very toxic to aquatic life with long lasting effects.
H412 Harmful to aquatic life with long lasting effects.

Revision information

None.

Training information

Follow training instructions when handling this material.

Disclaimer

ITW Performance Polymers cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release.